



## D O U B L E   U N I V E R S A L   J O I N T

Double universal joint for transmitting uniform rotary motion from an input end-shaft to an output end-shaft having shaft axes intersecting with each other at a variable angle,.

To achieve uniformity of the transmitted motion, in the prior art the double universal joints have a central tooth attached at the input end-shaft coupled with a boring on the output end-shaft. The coupling takes place at the center of rotation having limited high stressed contact surfaces. On the other hand, the oil material follows the centrifugal power toward the outside areas, leaving the center at the beginning of rotation.

It is an object of the invention to create unlimited contact surfaces for low stressed areas and to locate said areas at a distance to the axes of rotations.

*Page .1. of 10 pages*

*APPL. No : 10/816, 858*

According to the invention

- two input ~~tooth-wheels~~ <sup>swingers</sup> are rotatably mounted at one end of a middle-shaft about a cross-pivot-axis, and two output ~~wheels~~ <sup>swingers</sup> are mounted at the other end of the same middle-shaft about the other cross-pivot axis,

- bevel teeth are mounted on each ~~tooth-wheel~~ <sup>swinger</sup>. Bevel teeth are mounted on each end-shaft, coupled with the respective two ~~bevel tooth-wheels~~ <sup>swingers</sup> on the respective middle-shaft end, for turning of each two input- and each ~~output tooth-wheel~~ <sup>two, swingers</sup> at same direction about the respective input- and output middle cross-axis when the output end-shaft is turning about the respective input- and output middle cross-axis, and for turning of the same ~~tooth-wheels~~ <sup>two swingers</sup> at two opposite directions when the respective end-shaft is turning about the respective end cross-axis.

Parallel teeth are mounted on each ~~tooth-wheel~~ <sup>swinger</sup> for coupling of each two ~~wheels~~ <sup>swingers</sup> located at two difference middle-shaft ends for symmetrically transmitting of each input end-shaft direction to the output end-shaft direction for transmitting of uniform motion.

*According to the*

After the invention ~~to~~ <sup>the</sup> contact surfaces are unlimited and low stressed areas and located at a distance to the axes of rotations being able to keep the oil on the contact surfaces.

The following description of a preferred embodiment will show the principle of the invention.

Fig. 1 is a longitudinal-section <sup>A-A</sup> according to Fig. 2,  
Fig. 2 is a cross-section <sup>B-B</sup> of the output <sup>t</sup> area, according to Fig. 1,  
Fig. 3 is a cross-section <sup>C-C</sup> of the input area, according to Fig. 1  
Fig. 4 is a perspective picture of a part of the invention about the output area.

The double universal joint has an input end-shaft 1 transmitting non uniform motion to the middle-shaft 3 and uniform motion to the output end-shaft 2. The two ends of the middle shaft 3 are provided with sleeves 12, 13, 14, 15 having an input middle cross-axis 46 and an output middle cross-axis 48.

Input end-shaft 1 has a fork 6 with two sleeves 7, 8 and output end-shaft 2 has a fork 9 with two sleeves 10, 11. The two sleeves 7, 8 have a common end cross-axis 45 and the two sleeves 10, 11 have a common end cross-axis 47. An input pivot-cross 16 and an output pivot-cross 17 interconnect the three shafts 1, 2, 3 with each other.

The input pivot-cross 16 has pivots 18, 19 with a middle cross-axis 46 rotatably mounted in the two sleeves 12, 13 of the <sup>input</sup> ~~one~~ end of the middle shaft 3 and pivots 20, 21 with end cross-axis 45 are rotatably mounted in the two sleeves 7, 8 of the fork 6 of the input end-shaft 1.

The output pivot-cross 17 has pivots 22, 23 with middle cross-axis 48 rotatably mounted in the two sleeves 14, 15 of the <sup>output</sup> ~~other~~ end of the middle shaft 3 and pivots 24, 25 with end-cross-axis 47 rotatably mounted in the two sleeves 10, 11 of the fork 9 of the output end-shaft 2.

According to the invention, the sleeves 7, 10 are provided with bevel-teeth 34, 35 ~~for coupling with bevel-teeth 36, 37 and 38, 39.~~

Two input swingers 26, 27 <sup>7</sup> provided with parallel teeth 30, 31 ~~for coupling with each other~~ are rotatably mounted on the pivots 18, 19 ~~about~~ <sup>about</sup> middle cross-axis 46 and two output swingers 28, 29 provided with teeth 32, 33 ~~for coupling with each other~~ <sup>for coupling with input swingers 26, 27</sup> are rotatably mounted on the pivots 22, 23 ~~with~~ <sup>about</sup> middle cross-axis 48.

All swingers 26, 27, 28, 29 have in addition bevel teeth 36, 37, 38, 39 for coupling with end-shaft sleeves 7, 10 for turning of each two input swingers 26, 27 and each two output swingers 28, 29 at same direction about the respective input and output middle cross-axis 46 and 48 when the input and output end-shaft 1, 2 are turning about the respective input and output middle cross-axes 46, 48 and for turning the two input and output swingers 26, 27 and 28, 29 at two opposite directions about the respective input and output middle cross-axis 46, 48 when the input and output end-shaft 1, 2 are turning about the respective end cross-axes 45, 47. The <sup>parallel</sup> teeth couplings of each input swinger 26, 27 with the respective output swingers 28, 29 result to

page -4- of 10 pages

App'l. No.: 80/816,858

symmetrically transmitting of each input end-shaft direction to the output end-shaft direction for transmitting of uniform motion.

More embodiments are possible with combinations of different constructions without departing from the principle idea of the invention.